

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	MKT Metall-Kunststoff-Technik GmbH & Co. KG
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-MKT-20250487-CBA1-EN
Issue date	13.08.2025
Valid to	28.04.2030

VMH

MKT Metall-Kunststoff-Technik GmbH & Co. KG

www.ibu-epd.com | <https://epd-online.com>



...eine starke Verbindung

General Information

MKT Metall-Kunststoff-Technik GmbH&Co. KG

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-MKT-20250487-CBA1-EN

This declaration is based on the product category rules:

Reaction resin products, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

13.08.2025

Valid to

28.04.2030



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

VMH

Owner of the declaration

MKT Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
67685 Weilerbach
Germany

Declared product / declared unit

The declared product is the 2-component reaction resin mortar VMH from MKT Metall-Kunststoff-Technik GmbH&Co. KG. The declared unit refers to 1 kg of reaction resin product in the mixing ratio of the two components required for processing. The cartridge system is also included in the calculation, as the product is sold as a system by MKT Metall-Kunststoff-Technik GmbH&Co. KG. The declared unit is given in [kg].

Scope:

This document refers to the 2-component reaction resin mortar VMH. For the preparation of the life cycle assessment, specific data was collected from the manufacturing plant of MKT Metall-Kunststoff-Technik GmbH&Co. KG. Data from 2023 are used, which correspond to the annual average. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
☐	internally
☒	externally



Angela Schindler,
(Independent verifier)

Product

Product description/Product definition

The declared product VMH mortar is a 2-component reaction resin mortar based on a urethane methacrylate resin and a hardener and will be delivered in a 2- component cartridge system.

This high-performance product may be used in combination with a hand-, battery- or pneumatic tool and a static mixer. It was designed especially for the anchoring of threaded rods, reinforcing bars or internal threaded rod sleeves into concrete. Based on the excellent standing behaviour the usability for overhead application is given. The 2-component reaction resin mortar VMH is characterised, by a huge range of applications including seismic actions C1 + C2 with an installation temperature from -5°C to +40°C and an application temperature up to 160°C as well as by high chemical resistance for applications in extreme environments e.g. in swimming pools (chlorine) or in closeness to the sea (salt). For the placing of the product on the market in the EU/EFTA (with the exception of Switzerland) the Construction Products Regulation (CPR), Regulation (EU) No. 305/2011, is valid. The product requires a declaration of performance taking into account ETA-17/0716, ETA-17/0715 and the CE marking.

Application

The declared product VMH is used for the secure fixation of threaded rods, internal threaded rod sleeves and subsequently mortared reinforcement connections in cracked and noncracked concrete C20/25 to C50/60 for a working life of up to 100 years and is suitable for installation in hammer-drilled (standard SDS and hollow-core drill) holes at a temperature in the anchoring base between -5°C and 40°C.

Applications samples:

Suitable for the fixation of facades, roofs, wood constructions, metal constructions; metal profiles, columns, beams, consoles, railings, sanitary devices, cable trays, piping, post-installed rebar connection (reconstruction or reinforcement), etc.

Technical Data

The following structural data are relevant for the declared product VMH in the delivery state:

Construction Data

Name	Value	Unit
Density acc. to DIN 51757 for mixing the two components	1,7	g/ml
Compressive strength acc. to DIN EN 196 Part 1	126	N/mm ²
Flexural strength acc. to DIN EN 196 Part 1	22	N/mm ²

Storage:

Store in a cold, dry and dark place; storage temperature: from +5 °C to +25 °C

Shelf life:

18 months in standard cartridge systems

Gel and working time:

-5 °C 50 min.
0 °C 25 min.
+5 °C 15 min.
+10 °C 10 min.
+15 °C 6 min.
+20 °C 3 min.
+30 °C 2 min.

Full curing time in dry base material:

-5 °C 300 min.
0 °C 210 min.
+5 °C 120 min.
+10 °C 60 min.
+15 °C 40 min.
+20 °C 30 min.
+30 °C 30 min.

For more information, please refer to the valid technical data sheet.

Performance values of the product in accordance with the Declaration of Performance relating to its essential characteristics in accordance with ETA-17/0716 and ETA-17/0715 European Technical Assessment MKT Metall-Kunststoff-Technik GmbH&Co. KG VMH.

Base materials/Ancillary materials

The declared product VMH is delivered in the form of a 2-component cartridge system and consists of a resin component and a hardener component in a volume ratio of 10:1. The mixing ratio of resin and hardener component is automatically adjusted during the squeezing process. Curing begins immediately after the components are mixed.

1)The article/product/at least a partial product contains substances on the ECHA list of Substances of Very High Concern (SVHC) (27/06/2024) of more than 0.1% by weight: no.

2) The article/product/at least a partial product contains other CMR substances of category 1A or 1B that are not on the Candidate List of more than 0.1% by weight in at least a partial produce: no.

3) Biocidal products have been added to the construction product in question, or it has been treated with biocidal products (it is therefore a treated article within the meaning of the Biocidal Products Regulation (EU) No. 528/2012): no.

The product considered in this EPD contains the individual components in the following ranges:

Resin component:

Urethane methacrylate resin: 30 to 35 wt. %
Mineral fillers: 40 to 60 wt. %
Other components: < 5 wt. %

Hardener component:

Dibenzoyl peroxide: 10 to 15 wt. %
Mineral fillers: 45 to 65 wt. %
Other components: 10 bis 20 wt. %

Reference service life

The declared product VMH is exposed to different environmental conditions during the use phase. The expected reference working life depends on the specific installation situation and the associated exposure of the product. The main factors influencing the working life are weather and mechanical and chemical exposure.

LCA: Calculation rules

Declared Unit

The declared product here is a 2-component reaction resin mortar from MKT Metall-Kunststoff-Technik GmbH&Co. KG with the designation VMH. The declared unit refers to 1 kg of reaction resin product in the mixing ratio of the two components required for processing. The cartridge, based on 1 kg of reaction resin product, is also included in the calculation with 0.1531 kg.

Declared unit data

Name	Value	Unit
Declared unit	1	kg
conversion factor	1	-
gross density	1700	kg/m ³

System boundary

Type of EPD: cradle to gate with modules C1-C4 and module D. The following information modules are defined as system boundaries in this study:

Production stage (A1–A3):
A1, raw material extraction,
A2, transport to the manufacturer,
A3, manufacturing.

End of life stage (C1–C4):
C1, removal/demolition,
C2, transport,
C3, waste treatment,
C4, disposal.

Reuse, recovery and recycling potential (D)

In order to accurately capture the indicators and environmental impacts of the declared unit, a total of 8 information modules are considered. The information modules A1 to A3 describe the material provision, transport to the production site and the production processes of the product itself.

The intermediate products are sourced from Europe. The transport is carried out exclusively by truck. The following flow diagrams illustrate the production process on which this is based.




Figure 1 Information modules A 1 to A3 of the product




Figure 2 Information Modules A 1 to A3 of the cartridge

Information modules C1 to C4 cover the removal or demolition of the building, transport to waste disposal, waste treatment and disposal of the product. Furthermore, reuse, recovery and recycling potential are shown in Information module D.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Europe

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. LCA for Experts (Sphera) and ecoinvent 3.9.1 databases were used, documented in <https://lcadatabase.sphera.com/> und <https://ecoquery.ecoinvent.org/3.9.1/cutoff/search>

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

In the product and in the cartridge no renewable raw materials are used. Therefore, the biogenic carbon is reported as zero.

Cartridge per declared unit

Name	Value	Unit
Cartridge material PA6	0,0975	kg
Material of cartridge and cartridge components PP	0,0274	kg
Material of cartridge components HDPE/LDPE	0,0282	kg

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

End of Life (C1-C4)

The demolition of the product is carried out by means of an electric chisel. The electrical energy consumption for the tool is assumed to be 0.05 MJ for the declared unit. The electricity consumption is calculated using a European electricity mix. The construction waste is transported 200 km to the waste treatment plant by truck. In the waste treatment plant, the construction waste is shredded and then disposed.

Name	Value	Unit
Collected as mixed construction waste	1	kg
Shredding in the shredder	1	kg
Disposal	1	kg

Reuse, recovery and recycling potential (D), relevant scenario information

Name	Value	Unit
Reuse, recovery and recycling potentials	0	kg

LCA: Results

The impact assessment of the environmental loads is carried out in accordance with EN 15804+A2. The selection of characterization factors is based on PCR (EF3.1).

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	MND	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg VMH

Parameter	Unit	A1-A3	C1	C2	C3	C4	D
Global Warming Potential total (GWP-total)	kg CO ₂ eq	2.77E+00	6.96E-03	1.87E-02	2.72E-03	1.46E-02	0
Global Warming Potential fossil fuels (GWP-fossil)	kg CO ₂ eq	2.73E+00	6.96E-03	1.84E-02	2.68E-03	1.45E-02	0
Global Warming Potential biogenic (GWP-biogenic)	kg CO ₂ eq	3.65E-02	1.57E-06	0	0	0	0
Global Warming Potential luluc (GWP-luluc)	kg CO ₂ eq	1.51E-03	1.04E-06	3.04E-04	3.63E-05	8.71E-05	0
Depletion potential of the stratospheric ozone layer (ODP)	kg CFC11 eq	3.4E-05	7.65E-14	1.82E-15	4.84E-15	3.92E-14	0
Acidification potential of land and water (AP)	mol H ⁺ eq	6.56E-03	1.63E-05	7.07E-05	1.34E-05	1.03E-04	0
Eutrophication potential aquatic freshwater (EP-freshwater)	kg P eq	1.75E-04	3.64E-09	7.72E-08	1.04E-08	3.3E-08	0
Eutrophication potential aquatic marine (EP-marine)	kg N eq	1.58E-03	2.73E-06	3.32E-05	6.18E-06	2.65E-05	0
Eutrophication potential terrestrial (EP-terrestrial)	mol N eq	1.78E-02	2.92E-05	3.72E-04	6.83E-05	2.92E-04	0
Formation potential of tropospheric ozone photochemical oxidants (POCP)	kg NMVOC eq	6.04E-03	8.13E-06	6.57E-05	1.71E-05	8.12E-05	0
Abiotic depletion potential for non fossil resources (ADPE)	kg Sb eq	3.01E-06	3.29E-10	1.54E-09	2.81E-09	9.41E-10	0
Abiotic depletion potential for fossil resources (ADPF)	MJ	5.51E+01	1.29E-01	2.36E-01	5.02E-02	1.91E-01	0
Water use (WDP)	m ³ world eq deprived	2.62E-01	3.98E-04	2.69E-04	5.13E-04	1.66E-03	0

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg VMH

Parameter	Unit	A1-A3	C1	C2	C3	C4	D
Renewable primary energy as energy carrier (PERE)	MJ	3.75E+00	1.84E-02	2E-02	5.35E-03	3.34E-02	0
Renewable primary energy resources as material utilization (PERM)	MJ	0	0	0	0	0	0
Total use of renewable primary energy resources (PERT)	MJ	3.75E+00	1.84E-02	2E-02	5.35E-03	3.34E-02	0
Non renewable primary energy as energy carrier (PENRE)	MJ	4.2E+01	1.29E-01	2.36E-01	5.02E-02	7.8E+00	0
Non renewable primary energy as material utilization (PENRM)	MJ	1.31E+01	0	0	0	-7.61E+00	0
Total use of non renewable primary energy resources (PENRT)	MJ	5.51E+01	1.29E-01	2.36E-01	5.02E-02	1.91E-01	0
Use of secondary material (SM)	kg	0	0	0	0	0	0
Use of renewable secondary fuels (RSF)	MJ	0	0	0	0	0	0
Use of non renewable secondary fuels (NRSF)	MJ	0	0	0	0	0	0
Use of net fresh water (FW)	m ³	1.3E-02	2.59E-05	2.24E-05	1.49E-05	5.07E-05	0

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2:

1 kg VMH

Parameter	Unit	A1-A3	C1	C2	C3	C4	D
Hazardous waste disposed (HWD)	kg	7.16E-09	1.83E-11	7.64E-12	7.26E-12	4.77E-11	0
Non hazardous waste disposed (NHWD)	kg	2.42E-02	3.2E-05	3.67E-05	1.38E-05	9.71E-01	0
Radioactive waste disposed (RWD)	kg	4.62E-04	1.67E-05	3.05E-07	6.31E-07	2.01E-06	0
Components for re-use (CRU)	kg	0	0	0	0	0	0
Materials for recycling (MFR)	kg	0	0	0	0	0	0
Materials for energy recovery (MER)	kg	0	0	0	0	0	0
Exported electrical energy (EEE)	MJ	5.04E-02	0	0	0	0	0
Exported thermal energy (EET)	MJ	1.12E-01	0	0	0	0	0

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:

1 kg VMH

Parameter	Unit	A1-A3	C1	C2	C3	C4	D
Incidence of disease due to PM emissions (PM)	Disease incidence	ND	ND	ND	ND	ND	ND
Human exposure efficiency relative to U235 (IR)	kBq U235 eq	ND	ND	ND	ND	ND	ND
Comparative toxic unit for ecosystems (ETP-fw)	CTUe	ND	ND	ND	ND	ND	ND

Comparative toxic unit for humans (carcinogenic) (HTP-c)	CTUh	ND	ND	ND	ND	ND	ND
Comparative toxic unit for humans (noncarcinogenic) (HTP-nc)	CTUh	ND	ND	ND	ND	ND	ND
Soil quality index (SQP)	SQP	ND	ND	ND	ND	ND	ND

Restriction Note 1 — applies to the indicator 'Potential effect of human exposure to U235'. This effect category mainly deals with the possible effect of low dose ionizing radiation on human health in the nuclear fuel cycle. It does not take into account the effects of possible nuclear accidents and occupational exposure, nor of the disposal of radioactive waste in underground facilities. The potential ionising radiation emitted by soil, radon and some construction materials is also not measured by this indicator.

Restriction Note 2 — applies to the indicators: 'Potential for scarcity of abiotic resources - non-fossil resources', 'Potential for scarcity of abiotic resources - fossil fuels', 'Water deprivation potential (user)', 'Potential comparative toxic unit for ecosystems', 'Potential comparative toxic unit for humans - carcinogenic effect', 'Potential comparative toxic unit for humans - non-carcinogenic effect', 'Potential soil quality index'. The results of these environmental impact indicators need to be applied with caution because the uncertainties of these results are high or because there is limited experience with the indicators.

References

DIN 51757

DIN 51757:2011-01, Testing of mineral oils and related materials - Determination of density.

EN 196

DIN EN 196-1:2016-11, Methods of testing cement - Part 1: Determination of strength.

ISO 14025

DIN EN ISO 14025:2011-10, Environmental labels and declarations - Type III environmental declarations - Principles and procedures

ISO 14044

DIN EN ISO 14044:2006-10, Environmental management - Life cycle assessment - Requirements and guidelines (ISO 14044:2006); German and English version EN ISO 14044:2006.

EN 15804

DIN EN 15804:2019-04+A2 (in print), Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products.

EN/TR 15941

CEN/TR 15941:2010-03, Sustainability of construction works - Environmental product declarations - Methodology for selection and use of generic data; German version CEN/TR.

ECHA list

www.echa.europa.eu

ecoinvent 3.9.1

Background database: ecoinvent 3.9.1
Zurich: ecoinvent (Ed.)
<http://www.ecoinvent.org>

ETA-17/0716

European Technical Assessment.

ETA-17/0715

European Technical Assessment.

IBU 2021

General Instructions for the EPD Program of the Institut Bauen und Umwelt e.V., version 2.0, Berlin: Institut Bauen und Umwelt eV., 2021.
www.ibu-epd.com

PCR Part A

Product category rules for construction products and services - Part A: Calculation rules for life cycle assessment and background report requirements, V1.4. Berlin: Institut Bauen und Umwelt e.V. (Ed.), 04/2024.

PCR: Reaction resin products

Product category rules for building-related products and services - Part B: Environmental product declaration requirements for reactive resin products, version 1.3.
Berlin: Institut Bauen und Umwelt e.V. (Ed.), 08/2024.

Sphera

LCA for Experts, Software and Database.
Leinfelden-Echterdingen; Sphera Solutions GmbH (Ed.)
Product Sustainability Data Search | Sphera (GaBi)
(version: 2024.2)

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council
of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

FIT-Umwelttechnik GmbH
Westerstr. 13
38442 Wolfsburg
Germany

05362 72 69 474
bertram@fit-umwelttechnik.de
www.fit-umwelttechnik.com



... eine starke Verbindung

Owner of the Declaration

MKT Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
67685 Weilerbach
Germany

+49 6374 9116-0
info@mkt.de
www.mkt.de